



STEALTH PATIO THEATER

α- ° Qih° u@ 'u=- ° u-k' y~@ ° u-OM'U ° Vy, O
(přeloženo pro SPT-P3-155 5.1, ovšem je i pro menší modely SPT-P3-103 5.1, SPT-P3-130 5.1)

DŮLEŽITÉ! Před použitím systému Patio Theater si pečlivě přečtěte následující pokyny.

h

o o h u
t

- . . .

h



h

yh

#

)\† V



If your system has been equipped with the Stealth Patio Theater RF Remote, you may use it to raise, lower or stop the screen. The screen will turn on or off automatically when raised or lowered.

1-Press the LIST button. This will show and highlight “Custom Buttons” on the remote control display.

2-Press the SELECT button. This will show and highlight “Lift Control” on the remote control display.

3-Press the SELECT button again. This will show 3 options on the remote control display; “Lift Up”, “Lift Down” and “Stop”. Use the Up/Down Arrows to highlight the required lift function then press SELECT to activate the function.

Note: If your installer has connected the system to a 3rd-party control system, please refer to that control systems’ instructions for using the Patio Theater. Ensure that the source and system headend equipment are turned on before using the display.

- **CAUTION!** – Please observe the below guidelines when raising or lowering your Stealth Patio Theater:
- **Never activate the screen unless you are nearby and have a clear view of the screen during the entire time the screen is in motion!**
- **Press the Red “Emergency Stop” button on the display to immediately stop the display lifts if anything is keeping the screen from freely and fully raising or lowering, or, if any unusual mechanical noises occur when the screen is in motion.**

Emergency Stop Button



- **Do not attempt to continually raise and lower the screen repeatedly; excessive repeated activations of the lifting mechanisms can lead to pre-mature system failure.**
- **Stand clear of the display when it is raising and lowering and never place anything on top of the display or anywhere on the enclosure at any time.**
- **Observe and respect the audible “Caution Screen Is Descending” notifications emanating from the screen enclosure when the display is being lowered.**

Source Selection and Volume Control

You use the provided Denon 500AV Processor for source selection and volume control. The AV processor is usually in an equipment rack located away from the display – ask your installer to identify the location of the AV processor and available sources. Refer to the Denon DN 500AV user manual provided with your system for additional information.



Select a source at the AV processor by using the left hand dial to scroll through the available source inputs.

Note: If your installer has connected the AV processor to a 3rd-party control system, please refer to that control systems' instructions for controlling the AV processor.

Control the system volume at the AV processor by using the right hand dial to scroll through the available source inputs.

Rain Sensor



The system has a rain sensor attached to the display enclosure. In some installations the rain sensor may be located elsewhere for best operation – consult your installing Dealer for rain sensor location. This sensor will automatically lower the screen if it senses rain or excessive moisture. ***Do not block or attempt to bypass this sensor, as the system is not designed to operate when water is present on the display. If any issues arise regarding the rain sensor function, please contact your authorized Stealth Acoustics Dealer.***

Windy Conditions

- ***Caution! The system is not intended to be used in winds over 5-10mph!!! Do not use the system in inclement weather or when higher winds are present or expected. If excessive winds come up during usage, immediately bring the screen down using the Red POWER button on the remote control or the LOWER SCREEN button on the screen enclosure.***

System Viewing

You can view your Patio Theater at any time of day, even in broad daylight. ***Avoid using the system when sunlight is directly on the screen.***

Your Patio Theater is best viewed at a distance from the screen. ***Proper minimum viewing distance usually ranges between 25-35 feet away, depending on the viewer.***

Always lower the screen when not in use! Never leave the screen un-attended in its up position!

System Maintenance

- There are no user-serviceable internal components of the display and all non-cosmetic maintenance must be performed by an authorized factory dealer. ***Opening of the screen enclosure back, making internal adjustments, or maintaining the LED display components by anyone other than an authorized Stealth service representative or authorized Stealth Dealer may void the system warranty.***
- You should have the system examined by your Stealth Dealer at least twice a year, preferably at the beginning of the usage season and at the end of the usage season. If the system is utilized year round, have the system examined at least every 6-months.
- A parcel of spare parts, including spare LED modules, power supply, etc. is provided with each system for future service needs. These spares should remain with the system for use only by authorized service personnel. ***Do not remove or relocate the spare parts parcel – doing so may delay timely service of your system.***
- The screen enclosure exterior should be kept clean, neat and sealed. You can extend the look and longevity of the screen enclosure just like any exterior portion of your home, by carefully washing the enclosure when dirty, or touching up the finish, etc.
- Check periodically for any externally visible changes in the enclosure, including, the display top where it meets the enclosure; the top should rest completely on the enclosure without any gaps. There should be no visible cracks or openings in the enclosure. In the unlikely event of small cracks, you can seal these with exterior painters caulk and then touch up the final finish.
- Listen periodically to the lifting mechanism when raising or lowering the screen. ***Stop the lift immediately using either the STOP button or the red EMERGENCY STOP button if any unusual motion is seen or if unusual noise is heard when activating the screen lifts and contact your dealer immediately.***

Customer Support

Your first line of customer support is your installing Stealth Authorized Dealer. Please contact them for any maintenance, service or assistance on proper system usage.

For further support, contact Stealth Acoustics:

+1 360-848-6800 support@stealthacoustics.com or www.stealthacoustics.com